



## TIMKEN AXLE CORP.



1.181 Inch | 30 Millimeter x 2.441 Inch | 62  
Millimeter x 0.937 Inch | 23.8 Millimeter SKF  
E2.3206 A-2ZTN9/C3 Angular Contact Ball  
Bearings

Bearing No. E2.3206 A-2ZTN9/C3

E2.3206 A-2ZTN9/C3 Bearing 2D drawings and 3D  
CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.303
EAN	7316574722952
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 23.8MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC



## TIMKEN AXLE CORP.

	1   ISO P0; No Filling Slot; No Snap Ring; C3-Loose; Polyamide Cage; 30 Degree
Other Features	Energy Efficient Bearing
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	E2.3206 A-2ZTN9/C3
B	0.937 Inch   23.8 Millimeter
d	1.181 Inch   30 Millimeter
D	2.441 Inch   62 Millimeter
bore diameter:	30 mm
cage material:	Fiberglass Reinforced Nylon
outside diameter:	62 mm
outer ring width:	23.8 mm
overall width:	0.9375 in
maximum rpm:	10000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Double Shield
fillet radius:	1 mm
radial dynamic load capacity:	30 kN
series:	E2.32
radial static load capacity:	20-2/5 kN