



TIMKEN AXLE CORP.

0.394 Inch | 10 Millimeter x 1.181 Inch | 30 Millimeter x 0.563 Inch | 14.3 Millimeter SKF 3200 A-2RS1TN9/C3 Angular Contact Ball Bearings



Bearing No. 3200 A-2RS1TN9/C3

3200 A-2RS1TN9/C3 Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.056
EAN	7316573930747
Product Group	B00152
Enclosure	2 Seals
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	10MM Bore; 30MM Outside Diameter; 14.3MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot;



TIMKEN AXLE CORP.

	No Snap Ring; C3-Loose; Polyamide Cage; 30 Degree; 1 (Sin
Other Features	NBR Contact Seal Glass Fibre Reinforced Cage
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	3200 A-2RS1TN9/C3
Weight / LBS	0.1238
D	1.181 Inch 30 Millimeter
d	0.394 Inch 10 Millimeter
B	0.563 Inch 14.3 Millimeter
bore diameter:	10 mm
operating temperature range:	-40 to +210 ° F
outside diameter:	30 mm
cage material:	Fiberglass Reinforced Nylon
overall width:	0.5625 in
outer ring width:	14.3 mm
row type & fill slot:	Double-Row Non-Fill Slot
maximum rpm:	17000 RPM
internal clearance:	C3
finish/coating:	Uncoated
closure type:	Double Seal
precision rating:	Not Rated
radial dynamic load capacity:	7.61 kN
fillet radius:	0.6 mm
radial static load capacity:	4.3 kN



TIMKEN AXLE CORP.

series:		32
---------	--	----