



TIMKEN AXLE CORP.

9SRS20GM+[51-900/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 9SRS20GM+[51-900/1]LM

9SRS20GM+[51-900/1]LM Bearing 2D drawings and 3D CAD models

| | |
|----------------------------------------------|------------------------------|
| Days to Ship | 22 Days |
| Block Type | [Standard] M: Compact |
| The number of LM blocks combined with a axis | 9 |
| Nominal Part Number | 20 |
| Rail Type | Standard |
| Rail Width W1 | 20 mm |
| Mounting Height M | 20 mm |
| Rail Length L | 51 ~ 900 mm |
| Radial Clearance | Normal |
| Accuracy Grade | Normal Grade (Best Leadtime) |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 5950 |
| Basic Load Rating Static Rating Co(N) | 9400 |
| Allowable Static Moment MA(N m) | 44.7 |
| Allowable Static Moment MB(N m) | 53.3 |
| Allowable Static Moment MC(N m) | 91.4 |
| Symbols for Dust Resistance | None (Not Recommended) |
| Block external dimension W | 40 mm |
| Block external dimension L | 32 mm |



TIMKEN AXLE CORP.

| | |
|---------------------------------------|-------|
| Number of Block Mounting Holes(holes) | 4 |
| Mounting Hole Dimension S(M) | M4 |
| Mounting Hole Screw Depth | 6 mm |
| Block dimension L1 | 34 mm |